


G042 - AIRPLUME

Mechanical Protection Polyurethane



"It is possible that gloves marked with previous standards are despatched. Cofra grants that all productions do not have technical and quality differences."



MAXIMUM VERSATILITY



Features	<ul style="list-style-type: none"> Excellent dexterity and ease of movement 					
Coating	Polyurethane					
Lining	Polyester					
Gauge	13					
Colour	Grey/grey					
Application	Mechanical industry, assembly, packaging, warehouse					
Sizes	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
Length	22 cm	23 cm	24 cm	25 cm	26 cm	27 cm
	8,7"	9"	9,5"	9,9"	10,2"	10,6"
Packaging	<i>Code</i>			<i>Quantity</i>		
	G042-D100			1 dozen (12 single packed gloves)		
	G042-K100			Carton containing 12 dozen (144 single packed gloves)		

SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	RESULT REACHED
EN ISO 21420:2020	Protective gloves - General requirements and test methods	COMPLIANT

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED
		1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	3
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1
EN 388:2016+A1:2018	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	3
EN 388:2016+A1:2018	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	1
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	X
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P		ABSENT			ABSENT
		Achieved		Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved