

G042 - AIRPLUME
Mechanical Protection Polyurethane



EN 388:2003



2142

EN 388:2016



3131X

EN 420



"Following the new EU Regulation 2016/425 and the new standards on protective gloves EN 388:2016, EN ISO 374-1:2016, EN 374-2:2015 and EN 16523-1:2015, COFRA is re-certifying all its protective gloves. For this reason, it is possible that in our stock and on the market there are still gloves with the old standards EN 388:2003, EN 374-1:2003, EN 374-2:2003, EN 374-3:2003. COFRA guarantees that all the productions do not have technical and qualitative differences and are in compliance with the regulations in force"

Features	<ul style="list-style-type: none"> Excellent dexterity and ease of movement
-----------------	--

Coating	Polyurethane
----------------	--------------

Lining	Polyester
---------------	-----------

Gauge	13
--------------	----

Colour	White/white
---------------	-------------

Application	Assembly, packaging, painting works
--------------------	-------------------------------------

Sizes	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
--------------	--------	-------	-------	-------	---------	----------

Length	22 cm	23 cm	24 cm	25 cm	26 cm	27 cm
	8,7"	9"	9,5"	9,9"	10,2"	10,6"

Packaging	Code		Quantity			
	G042-D101		1 dozen (12 single packed gloves)			
	G042-K101		Carton containing 12 dozen (144 single packed gloves)			



MAXIMUM VERSATILITY



SAFETY TECHNICAL SPECIFICATIONS

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009 (par. 4.3.2)	pH determination (palm)	3,5 < pH < 9,5	6,6
EN 420:2003 + A1 2009 (par. 4.3.2)	pH determination (back)	3,5 < pH < 9,5	6,5
EN 420:2003 + A1 2009 (par. 4.3.2)	pH determination (cuff)	3,5 < pH < 9,5	6,6
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	< 5

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED	
		1	2	3	4	5		
EN 388:2016 (par. 6.1)	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	3	
EN 388:2016 (par. 6.2)	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1	
EN 388:2016 (par. 6.4)	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	3	
EN 388:2016 (par. 6.5)	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	1	
EN 388:2016 (par. 6.3) - EN ISO 13997	TDM : cutting resistance (N)	A ≥ 2	B ≥ 5	C ≥ 10	D ≥ 15	E ≥ 22	F ≥ 30	X
EN 388:2016 (par. 6.6) - EN 13594:2015	Impact protection	P Achieved		ABSENT Test not executed			ABSENT	

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved