

**G065 - BAJKAL**  
*Mechanical Protection Nitrile*



**MAXIMUM VERSATILITY**



<b>Features</b>	<ul style="list-style-type: none"> <li>Fully coated, waterproof</li> <li>Quick release system</li> <li>Reinforced safety cuffs</li> </ul>		
<b>Coating</b>	Nitrile		
<b>Lining</b>	Cotton		
<b>Cuff</b>	Reinforced safety cuffs		
<b>Colour</b>	White/navy		
<b>Application</b>	Building, construction, agriculture, waste collection and gardening		
<b>Sizes</b>	9 (L)	10 (XL)	11 (XXL)
<b>Length</b>	25 cm	26 cm	27 cm
	9,9"	10,2"	10,6"

<b>Packaging</b>	Code	Quantity
	G065-DD00	1 dozen (1 bag containing 12 pairs)
	G065-KD00	Carton containing 12 dozen (12 bags containing 12 pairs)

**SAFETY TECHNICAL SPECIFICATIONS**

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	RESULT REACHED
EN ISO 21420:2020	Protective gloves - General requirements and test methods	<b>COMPLIANT</b>

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED
		1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	<b>4</b>
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	<b>1</b>
EN 388:2016+A1:2018	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	<b>1</b>
EN 388:2016+A1:2018	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	<b>1</b>
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	<b>A</b>	<b>B</b>	<b>C</b>	<b>D</b>	<b>E</b>	<b>X</b>
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	<b>P</b>		<b>ABSENT</b>			<b>ABSENT</b>
		Achieved		Test not executed			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved