

G004 - CLING Mechanical Protection Nitrile











"It is possible that gloves marked with previous standards are despatched. Cofra grants that all productions do not have technical and quality differences."

Features

Lining

- High resistance to oils
- Excellent grip on dry surfaces

Coating Smooth nitrile

Polyester

Gauge 13

Colour Grey/black

Mechanical industry, building and construction, **Application** agriculture

Sizes	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)	
Lenght	23 cm	24 cm	25 cm	26 cm	27 cm	
	9"	9,5"	9,9"	10.2"	10.6"	



EXCELLENT GRIP ON DRY SURFACES



	(Code				Quantity			
	G00	4-D100	1 do	1 dozen (12 single packed gloves)					
Packaging	G004-DD00 1 dozen (1 bag containing 12 pairs)								
	G00	4-K100	Cart	Carton containing 12 dozen (144 single packed gloves)					
	G00	4-KD00	Cart	Carton containing 12 dozen (12 bags containing 12 pairs)					





SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	7,05
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	NOT RECORDING
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	COMPLIANT

STANDARD	DESCRIPTION			LEVEL					
STANDARD			1	2	3	4	5	REACHED	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)			≥ 500	≥ 2000	≥ 8000	-	3	
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)			≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	1	
EN 388:2016+A1:2018	Tear resistance (N)			≥ 25	≥ 50	≥ 75	-	4	
EN 388:2016+A1:2018	Puncture resistance (N)			≥ 60	≥ 100	≥ 150	-	2	
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	Α	В	С	D	Е	F	х	
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	≥ 30	^	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P			ABSENT			ABSENT	
	Impact protection		Achieved			not exec			

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved