




art.G126 – DENIM – Mechanical Protection



AZO FREE

HIGH QUALITY COW SPLIT LEATHER



Features	<ul style="list-style-type: none"> • Soft cow split • The back made of jeans fabric offers a better resistance to abrasion 		
Palm	High quality cow split leather		
Back	Cotton jeans		
Cuff	Reinforced safety cuffs		
Colour	Neutral / blue jeans		
Length	250 – 270 mm / 9,9” – 10,6”		
Leather Thickness	1,0 – 1,1 mm (The thickness of the material is not validating and it is not guaranteed, therefore any thickness variation cannot be reason of complaint, in consideration of the high variability of leather)		
Sizes	9 – 11 (L-XXL)		
Applications	handling of building materials, mechanical industry, agriculture		
Packaging	<i>code</i>	<i>quantity</i>	
	G126-DD00	1 dozen	1 bag containing 12 pairs
	G126-KD00	6 dozen	6 bags containing 12 pairs
Standards	  		

SAFETY TECHNICAL SPECIFICATIONS

Technical features	<i>test method</i>	<i>description</i>	<i>Cofra result</i>	<i>minimum requirement / range</i>
	EN 340:2003 par 4.3.2 (EN 4045)	PH determination of leather	3,85	3.5 < pH < 9.5
	EN 340:2003 par 4.1 (EN 1413)	PH determination of back	6,80	3.5 < pH < 9.5
	EN 340:2003 par 4.2 (CE ISO/TS 17234)	Chromium VI determination	Absent	< 10 [mg/Kg]
	EN 340:2003 par 4.2 (EN 14362-1)	Carcinogenic and aromatic amines	0 [ppm]	< 30 [ppm]
	EN 388:2003 par 6.1	Abrasion resistance	2	1 ÷ 4
	EN 388:2003 par 6.2	Blade cut resistance	1	1 ÷ 5
	EN 388:2003 par 6.3	Tear resistance	3	1 ÷ 4
	EN 388:2003 par 6.4	Puncture resistance	2	1 ÷ 4