



DUCTILE G050

MECHANICAL PROTECTION

Features:

Protective glove for mechanical works.
Highly versatile.
The lightweight and breathable 15-gauge lining gives the glove maximum dexterity.
The soft and flexible compound provides maximum comfort to the user's hands.
Without DMF.
Touch screen functionality, usable with capacitive and resistive devices (monitors, PDAs, tablets, smartphones).

Composition

Material: nitrile foam
Lining: polyester, elastane
Gauge: 15
Colour: blue, black

Application:

agriculture, animal farming, building and construction, electrical engineering, DIY, electronics industry, engineering industry, textiles and leather industry, cleaning and services, transport and logistics





EXCELLENT DEXTERITY -
MAXIMUM VERSATILITY

TOUCH SCREEN
FUNCTIONALITY



Packaging:

Code	Quantity
G050-D100	1 dozen (12 single packed gloves)
G050-DD00	1 dozen (1 bag containing 12 pairs)
 G050-K100	Carton containing 20 dozen (240 single packed gloves)
 G050-KD00	Carton containing 20 dozen (20 bags containing 12 pairs)

Sizes	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
Length	-	-	24cm	25cm	26cm	27cm
	-	-	9,5"	9,9"	10,2"	10,6"

Further technical features:



OEKO-TEX® is a voluntary certification of product through which the certified company commits itself to keep in time the safeness of its own products. The OEKO-TEX® 100 mark guarantees that the textiles (or accessories of the textiles, metallic ones included) do not contain or release harmful substances for the consumer (pesticides, heavy metals, formaldehyde, aromatic amines, allergyinducing dyestuffs and so on).

OEKO-TEX® certified gloves fully comply with the requirements of standard EN ISO 21420:2020 and they abide by the requirements of the attachment XVII of REACH (regulation 552:2009) having the textile product as area of pertinence.

DUCTILE G050

EN 388:2016
+A1:2018




4121X

MECHANICAL PROTECTION

Safety technical specifications: the PPE is in compliance with essential requirements of (EU) 2016/425 Regulation and the European harmonized standards EN ISO 21420:2020, EN 388:2016+A1:2018

EN ISO 21420:2020	Level	Result reached
Protective gloves - General requirements and test methods	-	COMPLIANT
Protective gloves - Dexterity	1-5	5
Textiles - Determination of pH of aqueous extract	3,5 ≤pH≤ 9,5	pH 7

EN 388:2016+A1:2018	Level						Result reached
	1	2	3	4	5		
 Abrasion resistance (number of frictions) Cutting test : blade cut resistance (index) Tear resistance (N) Puncture resistance (N) TDM: cutting resistance (N) Impact protection	≥100	≥500	≥2000	≥8000	-		4
	≥1,2	≥2,5	≥5,0	≥10,0	≥20,0		1
	≥10	≥25	≥50	≥75	-		2
	≥20	≥60	≥100	≥150	-		1
	A	B	C	D	E	F	X
	≥2	≥5	≥10	≥15	≥22	≥30	
P			ABSENT			ABSENT	
Achieved			Test not executed				

If one of the marking indexes is marked with:
 letter "X" means that the test wasn't executed or not applicable;
 number "0" means that the test was executed but the minimum performance level hasn't been achieved.