

G503 - GRABLIGHT
Disposable Gloves Nitrile



EN ISO 374-1 / Type B



K:6 > 480 min
L:1 > 10 min
O:2 > 30 min
P:2 > 30 min
T:6 > 480 min

EN ISO 374-5:2016



EN 420



KOPT



**TEXTURED EXTERNAL FINISH WITH
"DIAMONDS"**



Features	<ul style="list-style-type: none"> • 100% high quality nitrile disposable gloves, completely free of latex proteins • Textured external finish with "Diamonds" on both the palm and the back for better grip on all surfaces • Revolutionary and thicker (0,16 ÷ 0,20 mm) than traditional disposable gloves, they give good protection and performance • Maximum dexterity and perfect fit as well as being highly flexible
-----------------	--

Coating	Nitrile
----------------	---------

Internal finish	Powder-free
------------------------	-------------

External finish	Lozenges (Diamond)
------------------------	--------------------

Cuff	Rolled beaded
-------------	---------------

Colour	Light blue
---------------	------------

Lenght	240 mm / 9,4"
---------------	---------------

Thickness	6 mil (0,16 ÷ 0,20 mm)
------------------	------------------------

Sizes	7-11 (S-XXL)
--------------	--------------

Application	Product inspections, quality control, use of tempera, paint, varnishes, finishing, cleaning and maintenance
--------------------	---

Packaging	Code	Quantity
	G503-B000	1 box containing 100 pcs.
	G503-K000	Carton - 20 boxes containing 100 pcs.

SAFETY TECHNICAL SPECIFICATIONS

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009 (par. 4.3.2)	pH determination	3,5 < pH < 9,5	8,0

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 374-2:2014 (par. 7.2)	Determination of resistance to penetration - Air leakage test	COMPLIANT / NOT COMPLIANT	COMPLIANT
EN 374-2:2014 (par. 7.3)	Determination of resistance to penetration - Water leakage test	COMPLIANT / NOT COMPLIANT	COMPLIANT
EN 374-2:2014 (App. A)	Determination of resistance to penetration – Quality assurance during production (AQL)	Level 3 < 0,65 Level 2 < 1,5 Level 1 < 4,0	Level 2 < 1,5
EN ISO 374-1:2016 EN 16523-1:2015	Determination of material resistance to permeation by chemicals	Glove type	Type A / Type B / Type C
		Chemical	Type B
		Permeation performance level	1 2 3 4 5 6
		Measured crossing time (mins)	>10 >30 >60 >120 >240 >480
EN 374-4:2013	Determination of resistance to degradation by chemicals	---	7.3% 100% 6.1% 10.5% 0.9%
EN ISO 374-5:2016	Protective gloves against bacteria and fungi	COMPLIANT / NOT COMPLIANT	COMPLIANT
	Protective gloves against viruses	COMPLIANT / NOT COMPLIANT	NOT COMPLIANT (not tested)