

**G503 - GRABLIGHT**  
*Disposable Gloves Nitrile*



EN ISO 374-1 / Type B



KOPT

K:6 > 480 min  
L:1 > 10 min  
O:2 > 30 min  
P:2 > 30 min  
T:6 > 480 min

EN ISO 374-5:2016



EN 420



**Features**

- 100% high quality nitrile disposable gloves, completely free of latex proteins
- Textured external finish with “Diamonds” on both the palm and the back for better grip on all surfaces
- Revolutionary and thicker (0,16 ÷ 0,20 mm) than traditional disposable gloves, they give good protection and performance
- Maximum dexterity and perfect fit as well as being highly flexible

**Coating**

Nitrile

**Internal finish**

Powder-free

**External finish**

Lozenges (Diamond)

**Cuff**

Rolled beaded

**Colour**

Black

**Lenght**

240 mm / 9,4”

**Thickness**

6 mil (0,16 ÷ 0,20 mm)

**Sizes**

7-11 (S-XXL)

**Application**

Mechanical industry, assembly of small components, spray painting, electroplating, cleaning and maintenance, beauty institute, hairdressers, tattooists



**TEXTURED EXTERNAL FINISH WITH “DIAMONDS”**



**Packaging**

Code

Quantity

G503-B001

1 box containing 100 pcs.

G503-K001

Carton - 20 boxes containing 100 pcs.

**SAFETY TECHNICAL SPECIFICATIONS**

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009 (par. 4.3.2)	pH determination	3,5 < pH < 9,5	<b>7,9</b>

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 374-2:2014 (par. 7.2)	Determination of resistance to penetration - Air leakage test	COMPLIANT / NOT COMPLIANT	<b>COMPLIANT</b>
EN 374-2:2014 (par. 7.3)	Determination of resistance to penetration - Water leakage test	COMPLIANT / NOT COMPLIANT	<b>COMPLIANT</b>
EN 374-2:2014 (App. A)	Determination of resistance to penetration – Quality assurance during production (AQL)	Level 3 < 0,65 Level 2 < 1,5 Level 1 < 4,0	<b>Level 2 &lt; 1,5</b>
EN ISO 374-1:2016 EN 16523-1:2015	Determination of material resistance to permeation by chemicals	Glove type	Type A / Type B / Type C
		Chemical	Type B
		Permeation performance level	1 2 3 4 5 6
		Measured crossing time (mins)	>10 >30 >60 >120 >240 >480
EN 374-4:2013	Determination of resistance to degradation by chemicals	---	7.3% 100% 6.1% 10.5% 0.9%
EN ISO 374-5:2016	Protective gloves against bacteria and fungi	COMPLIANT / NOT COMPLIANT	<b>COMPLIANT</b>
	Protective gloves against viruses	COMPLIANT / NOT COMPLIANT	<b>NOT COMPLIANT (not tested)</b>