

**G043 - LIMBER**

*Mechanical Protection Polyurethane*



EN 388:2016  
+A1:2018



2111X

DEXTERITY



**PU-DEX**

**Features**

- Excellent dexterity and comfort
- Excellent breathability and ergonomics
- Excellent grip, recommended for the handling of small tools

**Coating**

Polyurethane PU-DEX

**Lining**

Nylon

**Gauge**

18

**Colour**

Navy/grey

**Application**

Small parts assembly, jobs demanding a prolonged use of gloves, warehouse, packaging

**Sizes**

6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (XXL)
--------	-------	-------	-------	---------	----------

**Lenght**

22 cm	23 cm	24 cm	25 cm	26 cm	27 cm
8,7"	9"	9,5"	9,9"	10,2"	10,6"

**Packaging**

Code	Quantity
G043-D100	1 dozen (12 single packed gloves)
G043-K100	Carton containing 10 dozen (120 single packed gloves)




**ULTRA-THIN - EXCELLENT DEXTERITY  
EVEN WITH VERY SMALL TOOLS**





New polyurethane compound that turns around the concept of grip. The excellent grasp of little tools and the maximum dexterity enhance productivity in those jobs where maximum precision and accuracy are demanded.



## SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination	3,5 < pH < 9,5	<b>7,7</b>
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	<b>&lt; 5</b>
EN ISO 21420:2020	Further technical specifications applied	COMPLIANT / NOT COMPLIANT	<b>COMPLIANT</b>

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED	
		1	2	3	4	5		
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	<b>2</b>	
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	<b>1</b>	
EN 388:2016+A1:2018	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	<b>1</b>	
EN 388:2016+A1:2018	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	<b>1</b>	
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	<b>A</b> ≥ 2	<b>B</b> ≥ 5	<b>C</b> ≥ 10	<b>D</b> ≥ 15	<b>E</b> ≥ 22	<b>F</b> ≥ 30	<b>X</b>
EN 388:2016+A1:2018- EN 13594:2015	Impact protection	<b>P</b> Achieved		<b>ABSENT</b> Test not executed			<b>ABSENT</b>	

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved