

G096 - MIDDLEL
Cut Protection Polyurethane



"It is possible that gloves marked with previous standards are despatched. Cofra grants that all productions do not have technical and quality differences."

Features	<ul style="list-style-type: none"> • Excellent cut resistance • High lightness and breathability • Lining without glass fibers • Soft polyurethane coating
-----------------	--

Coating	Polyurethane
----------------	--------------

Lining	Braided threads of polyethylene UHMWPE, polyester, stainless steel, nylon, elastane
---------------	---

Gauge	13
--------------	----

Colour	Grey/grey
---------------	-----------

Application	Building and construction, glassworks, mechanical industry, metal sheets, handling of sharp tools, signage, metal panels
--------------------	--

Sizes	8 (M)	9 (L)	10 (XL)	11 (XXL)
--------------	-------	-------	---------	----------

Lenght	24 cm	25 cm	26 cm	27 cm
	9,5"	9,9"	10,2"	10,6"



RESISTENZA AL TAGLIO E LEGGEREZZA



Packaging	<i>Code</i>	<i>Quantity</i>
	G096-D100	1 dozen (12 single packed gloves)
	G096-K100	carton containing 20 dozen (240 single packed gloves)

SAFETY TECHNICAL SPECIFICATIONS

The PPE is in compliance with essential requirements of (EU) 2016/425 regulation

STANDARD	DESCRIPTION	MINIMUM REQUIREMENT / RANGE	RESULT REACHED
EN 420:2003 + A1 2009	pH determination (palm)	3,5 < pH < 9,5	7,6
EN 420:2003 + A1 2009	pH determination (back)	3,5 < pH < 9,5	7,5
EN 420:2003 + A1 2009	pH determination (cuff)	3,5 < pH < 9,5	7,4
UNI EN 14362-1/3:2012	Carcinogenic and aromatic amines	≤ 30 ppm	< 5

STANDARD	DESCRIPTION	LEVEL					LEVEL REACHED
		1	2	3	4	5	
EN 388:2016+A1:2018	Abrasion resistance (number of frictions)	≥ 100	≥ 500	≥ 2000	≥ 8000	-	4
EN 388:2016+A1:2018	Cutting test : blade cut resistance (index)	≥ 1,2	≥ 2,5	≥ 5,0	≥ 10,0	≥ 20,0	X
EN 388:2016+A1:2018	Tear resistance (N)	≥ 10	≥ 25	≥ 50	≥ 75	-	4
EN 388:2016+A1:2018	Puncture resistance (N)	≥ 20	≥ 60	≥ 100	≥ 150	-	3
EN 388:2016+A1:2018 - EN ISO 13997	TDM : cutting resistance (N)	A	B	C	D	E	C
		≥ 2	≥ 5	≥ 10	≥ 15	≥ 22	
EN 388:2016+A1:2018 - EN 13594:2015	Impact protection	P			ABSENT		ABSENT
		Achieved			Test not executed		

If one of the marking indexes is marked with:

- letter "X" means that the test wasn't executed or not applicable;
- number "0" means that the test was executed but the minimum performance level hasn't been achieved