

art. G621 – SUNGUARD – Chemical Protection

Features	<ul style="list-style-type: none"> Internally flocked to provide greater comfort and sweat absorption “Diamond” slip resistant finishing on palm and fingers able to assure a greater grip both in dry and humid environments Recommended for those jobs where a good chemical protection is required Being thin and flexible, it provides a high sensitivity Suitable for food contact Low latex protein content (50 µg/g) 		
Coating	Latex		
Internal Finish	Flocked		
External Finish	Lozenges (Diamond)		
Cuff	Straight cuff		
Colour	Yellow		
Length	295 mm / 11,6”		
Thickness	0,50 mm (20 mil)		
Sizes	7 – 10 (S-XL)		
Application	handling chemicals, light assembly, assembly of small oil and fat free components, cleaning		
Packaging	<i>code</i>	<i>quantity</i>	
	G621-D100	1 dozen	12 single packed gloves
	G621-K100	12 dozen	144 single packed gloves



LOW LATEX PROTEIN CONTENT



Standards				

"Following the new EU Regulation 2016/425 and the new standards on protective gloves EN 388:2016, EN ISO 374-1:2016, EN 374-2:2015 and EN 16523-1:2015, COFRA is re-certifying all its protective gloves. For this reason, it is possible that in our stock and on the market there are still gloves with the old standards EN 388:2003, EN 374-1:2003, EN 374-2:2003, EN 374-3:2003. COFRA guarantees that all the productions do not have technical and qualitative differences and are in compliance with the regulations in force"

SAFETY TECHNICAL SPECIFICATIONS

	<i>test method</i>	<i>description</i>	<i>Cofra result</i>	<i>minimum requirement / range</i>
Technical features	EN 388:2003 par 6.1	Abrasion resistance	2	1 ÷ 4
	EN 388:2003 par 6.2	Blade cut resistance	1	1 ÷ 5
	EN 388:2003 par 6.3	Tear resistance	1	1 ÷ 4
	EN 388:2003 par 6.4	Puncture resistance	0	1 ÷ 4
	EN 374-2:2003 par. 5.2	Resistance to penetration (air leakage test)	compliant	compliant / not compliant
	EN 374-2:2003 par. 5.3	Resistance to penetration (water leakage test)	compliant	compliant / not compliant
	EN 374-2:2003	Resistance to micro-organisms	compliant	compliant / not compliant
	EN 374-3:2003	Resistance to permeation	A: 0 > 10 min K: 6 > 480 min L: 1 > 10 min	1 ÷ 6 (>10 min ÷ >480 min)
	Regulation (CE) 1935/2004	Suitable for food contact	compliant	compliant / not compliant
	US FDA CFR 21 Part 177-2600			